



RVS TECHNOLOGY® PREMIUM UNIVERSAL OIL.

Every can of RVS premium universal oil contains 150ml of a very efficient high-quality oil, containing RVS triboceramics, specifically developed for protection and restoration of metal surfaces. The RVS premium universal oil is a biodegradable oil, which when used correctly it penetrates well and produces a durable triboceramic protection layer on all metal friction surfaces. It resists high speed and will protect against water and rust.

Commonly used in the automotive, energy and manufacturing industries, RVS premium universal oil has three general applications:

Lubricating rapidly moving or sensitive machine parts;

Loosening threads on bolts, axles and other fasteners;

A water repellent/anti-corrosive coating.

RVS premium universal oil allows lubrication without adding resistance between parts. Also, with the aerosol spray, it's much easier to apply and reapply the oil to hard-to-reach places. When applied to stuck threads, the low-viscous oil will seep deep into the narrow places to dissolve encrusted residue and free the pieces. If a tightly fitting moving part is making noise, applying on the outside will seep into the microscopic space between the metal as a lubricating layer. Given its tendency to expand across surfaces in a uniform coat (caused by a phenomenon known as weak surface tension) as well as its natural ability to repel water molecules, RVS premium universal oil is effective at protecting iron and aluminium from rust. Machinists and engineers are well-aware of this added benefit, and frequently use it as a protectant for commercial and industrial products. RZVS premium universal oil can be used to free rusted mechanical parts (such as nuts and bolts) so that they can be removed, because it can penetrate into the narrow space between the threads of two parts. It can also be used as a general-purpose lubricant, a cleaner, or a corrosion stopper. Using RVS premium universal oil treatment as general-purpose lubricant is not advisable on its own as it should be used in conjunction with the specified lubricant already being used.

Spray the surface/surfaces to be treated liberally with RVS premium universal oil – if it is being used to free a nut and bolt or other seized items then leave the oil to soak in for five minutes or so before trying to free the piece.

Storage and safety instructions.

Extremely flammable aerosol – pressurised container. May burst if heated.

- + Store at temperatures below +40 °C (105°F). Do not expose to temperatures exceeding 50°C / 122°F. Protect from sunshine.
- + In case of skin contact, wash with lukewarm water and soap
- + If the product gets in your eyes, it may cause irritation, flush with copious amounts of water and if the irritation persists consult a doctor.
- + If the product is swallowed, flush the mouth with water and consult a doctor. Do not induce vomiting.
- + In case of fire all types of fire extinguisher should be used – except water.
- + Keep out of reach of children.
- + Keep away from heat/sparks/open flames/hot surfaces – no smoking whilst using the product